

SPA 12 - 7 | VRLA Battery



Applications

- Uninterruptible Power Supplies (UPS)
- Electric Power Systems (EPS)
- Emergency backup power supplies
- Electronic apparatus and equipment
- Communication power supplies
- DC power supplies
- Auto control system


Specifications

Nominal Voltage	12 V		
Number of cells	6		
Design Life	10 years		
Dimensions	Length		151 mm
	Width		65 mm
	Height		94 mm
	Total Height		100 mm
Approx. Weight	1.95 kg		
Nominal Capacity (25°C)	20 hours rate (0.35 A, 10.5 V)		7.00 Ah
	10 hours rate (0.62 A, 10.5 V)		6.20 Ah
	5 hours rate (1.12 A, 10.5 V)		5.60 Ah
	1 hour rate (4.29 A, 9.6 V)		4.29 Ah
Max. Discharge Current (25°C)	105 A (5s)		
Max. Charging Current (25°C)	2.1 A		
Internal Resistance	26 mOhms		
Fully Charged battery (25°C)			
Self-Discharge (25°C)	3% of capacity declined per month (average)		
Operating Temperature Range	Discharge	: -15~50°C	
	Charge	: -10~50°C	
	Storage	: -20~50°C	
Short Circuit Current	225 A		
Charging Characteristics (25°C)	Boost charging voltage		2.40-2.45 Vpc
	Temperature compensation		-30 mV/°C
	Float charging voltage		2.25-2.30 Vpc
	Temperature compensation		-18 mV/°C

Battery Construction

Component	Positive Plate	Negative Plate	Container	Cover	Safety Valve	Terminal	Separator	Electrolyte
Raw material	Lead dioxide	Lead	ABS	ABS	Rubber	Copper	Fiberglass	Sulfuric acid

Dimensions



Constant Current Discharge (Amperes) at 25°C

End Voltage (Volts/Cell)	5 min	10 min	15 min	30 min	1 h	2 h	3 h	4 h	5 h	10 h	20 h
1.60 V	25.1	15.8	12.5	7.00	4.29	2.34	1.68	1.35	1.14	0.63	0.35
1.65 V	24.3	15.4	12.2	6.86	4.23	2.33	1.67	1.34	1.14	0.63	0.35
1.70 V	23.3	14.7	11.8	6.65	4.12	2.31	1.66	1.33	1.13	0.63	0.35
1.75 V	22.3	14.1	11.4	6.49	4.04	2.28	1.65	1.32	1.12	0.62	0.35
1.80 V	21.1	13.3	10.8	6.25	3.91	2.22	1.60	1.28	1.09	0.61	0.34


Constant Power Discharge (Watts) at 25°C

End Voltage (Volts/Cell)	5 min	10 min	15 min	30 min	1 h	2 h	3 h	4 h	5 h	10 h	20 h
1.60 V	280	179	143	80.2	49.7	27.4	20.0	16.0	13.7	7.59	4.20
1.65 V	271	173	140	78.6	48.9	27.3	19.9	15.9	13.6	7.56	4.19
1.70 V	260	166	134	76.2	47.7	27.0	19.7	15.8	13.5	7.52	4.16
1.75 V	249	159	130	74.3	46.7	26.6	19.6	15.7	13.4	7.48	4.14
1.80 V	235	150	123	71.6	45.3	25.9	19.0	15.2	13.0	7.33	4.06


(Note) The above characteristics data are average values obtained within three charge/discharge cycles.

SPA 12 - 7 | VRLA Battery


Temperature Effects on Float Life




Self Discharge Characteristics




Discharge Characteristics (25°C)




Charging Characteristics (25°C)




Relationship Between Charging Voltage and Temperature




Relationship Between Open Circuit Voltage and Residual Capacity (25°C)



Cycle Service Life in Relation to Depth of Discharge



Temperature Effects on Capacity



SYSTEMS SUNLIGHT S.A.

Headquarters

2 Ermou & Nikis Str., Syntagma Sq.
105 63 Athens, Attica, Greece

T +30 210 6245400 F +30 210 6245409

Manufacturing Plant

672 00 Neo Olvio, Xanthi, Greece

T +30 25410 48100 F +30 25410 95446

Southeast Europe Industrial Sales

14B Menexedon Street,

145 64 Kato Kifisia, Greece

T +30 210 6245600 F +30 210 6245619

SUNLIGHT
Reliable Battery Solutions

www.systems-sunlight.com